



- “C”, “D” and “E” pads have been replaced with “F” pads.
- “C” and “D” links and bushings are compatible with all pads.
- “E-F” links and bushings are ONLY compatible with “E-F” pads.

Item	Description	Note
1	8.5" Welded Pad (3/4" Bars)	
1,2,3,4,5	8.5" Welded Pad Complete	1
1	10.5" Welded Pad (1" Bars)	
1,2,3,4,5	10.5" Welded Pad Complete (1" Bars)	1
1	11.5" Welded Pad (3/4" Bars)	
1,2,3,4,5	11.5" Welded Pad Complete	1
1	11.5" Welded Pad (1" Bars)	
1,2,3,4,5	11.5" Welded Pad Complete (1" Bars)	1
1	13.25" Pad (for 10.00 Tires)	
1,2,3,4,5	13.25" Pad Complete	1,3
1	13.25" Low Profile	5
1,2,3,4,5	13.25" Low Profile Complete	1,5
1	14.75" Pad (for 12.00 Tires)	
1,2,3,4,5	14.75" Pad Complete	1,3
1	15.5" Welded Pad (1" Bars)	
1,2,3,4,5	15.5" Welded Pad Complete (1" Bars)	1
1	16.00" Pad (for 14.00 Tires)	
1,2,3,4,5	16.00" Pad Complete	1,3
1	17.50" Pad (for 33-15.5 Tires)	
1,2,3,4,5	17.50" Pad Complete	1
1	19.00" Welded Pad (1080C Bobcat)	2
1,2,3,4,5	19.00" Pad Complete	1,2

Item	Description	Note
3	C Link (7/8" holes)	
3	D Link (1" holes)	
3	E-F Link (1 1/4" holes)	
4	C Bushing 7/8" (O.D.)	
4	D Bushing 1" (O.D.)	
4	E-F Bushing 1 1/4" (O.D.)	
5	C,D,E,F Carriage Bolt 1/2"x1 7/8" GR5	
2	C,D,E,F Nut 1/2" NF GR5 center lock	
6	Web Binder	
7	Web Binder Strap	
2	5C nut 5/8" NC GR5 top lock	4
5	5C Carriage Bolt 5/8"x2.5" GR8	4
3	5C Link (1 1/4" holes)	4
4	5C Bushing 1 1/4" (O.D.)	4

**Notes:**

1. Includes 2 Links, 4 Nuts, 4 Bolts, 4 Bushings
2. 5C
3. For use on F track only.
4. For use on 19.00 pads only.
5. For use on machines with limited clearances.