





FH-400 John Deere 8030T

Undercarriage Installation Instructions

Caution:

- Always use precaution when working around any equipment.
- Always wear safety glasses.
- Follow tractor manufacture's safety guidelines when installing this product.
 1. Read all instructions prior to installation.
 2. Remove weights and weight bracket from front of tractor if necessary.
 3. Position the undercarriage (U/C) under the tractor and center with the frame of the tractor.
 4. Lift the U/C until the holes on the tractor line up with the U/C holes.
 5. At the front of the tractor, use 4 - 20mm x 70mm bolts (PN: 16-1876) with a 3/4" washer (PN: 57-20747) on each bolt to attach the U/C to the front of the tractor. See attached diagram for clarification.
 6. Raise rear of undercarriage until holes on the tractor line up with the U/C holes.
Be sure that the U/C is tight against the tractor.
 7. Attach rear of U/C to tractor with 4 - 20mm x 60mm bolts (PN: 16-2487) with a 3/4" washer (PN: 57-20747) on each bolt.
 8. Attach the left and right side rails (PN: 44-11742) to the left and right sides of the U/C with 6 - 3/4" x 2-1/4" bolts (PN: 16-20219), 12 - 3/4" flat washers (PN: 57-20747), and 6 - 3/4" nuts (PN: 70-20607) for each side rail. See attached diagram for clarification.
 9. Start 6 - 16mm x 75mm bolts (PN: 16-1620075) with a 16mm flat washer (PN: 57-20825) on each bolt through the top holes of the left and right rail and the tractor frame. See attached diagram for clarification.
 10. Start 2 - 20mm x 70mm bolts (PN: 16-1876) with a 3/4" flat washer (PN: 57-20747) on each bolt through the lower two holes of the left and right rail and the tractor frame. See attached diagram for clarification.
 11. Once all bolts are installed, torque all 20mm bolts to 432 ft-lbs., all 16mm bolts to 269 ft-lbs., and all 3/4" bolts to 257 ft-lbs.
 12. After first 8 hours of use, re-torque all bolts.
 13. Check all fasteners regularly to ensure proper operation of equipment.

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF GROUSER PRODUCTS INC ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF GROUSER PRODUCTS INC IS PROHIBITED.



Item No.	Qty.	Part No.	Description
1	12	16-1620075	16mm x 2.00mm x 75mm Metric Hex Bolt Gr. 10.9
2	8	16-1876	20mm x 2.5mm x 70mm Metric Hex Bolt Gr. 10.9
3	12	16-20219	3/4" x 2-1/4" Hex Bolt Gr. 5 NC
4	4	16-2487	20mm x 2.5mm x 60mm Metric Hex Bolt Gr. 10.9
5	2	44-11742	FH-400 8030T - Side Rail
6	1	54-11750	FH-400 UC JD 8030T Series
7	36	57-20747	3/4" Flat Washer
8	12	57-20825	16mm Flat Washer
9	12	70-20607	3/4" Hex Center Lock Nut Gr. 5 NC



GROUSER PRODUCTS INC.

755 2nd Ave NW Phone 701.282.7710
 West Fargo, ND 58078 Fax 701.282.8131
 WWW.GROUSER.COM

TITLE: FH-400 JD 8030T U/C

Date: 12/22/2006 DWG. NO.: 11750-A